according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier

1.2

Version number: GHS 4.0

Trade name Registration number (REACH)

Replaces version of: 02/22/2022 (GHS 3)

Unique formula identifier (UFI)

Relevant identified uses

Uses advised against

not relevant (mixture) UFI: nicht zutreffend

SILIKONCOLOR

Relevant identified uses of the substance or mixture and uses advised against

Paint, coating and lacquer Observe technical data sheet

Observe technical data sheet

1.3 Details of the supplier of the safety data sheet

Baumit GmbH Wopfing 156 A-2754 Waldegg Austria

Telephone: +43 (0)501 888 0

This number is only available during office hours: Mon - Thu 07:00 AM - 05:00 PM Fri 07:00 AM - 12:00 PM

e-mail: office@baumit.com

e-mail (competent person)

office@baumit.com

1.4 Emergency telephone number

Poison	centre

Country	Name	Postal code/ city	Telephone	
Austria	Vergiftungsinformationszentrale an der 1. Medizinischen Universitätsklinik 24h Notruf Mo-So	1090 Wien	+43 (0)1 4064 343-0	



Revision 12/20/2022

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR



Revision 12/20/2022

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

H412

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word not required
- Pictograms not required

- Hazard statements

Harmful to aquatic life with long lasting effects.

- Precautionary statements

	<i>j</i> statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P260	Do not breathe spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P501	Dispose of contents/container in accordance with local/regional/national/inter- national regulations.
- Supplementa	l hazard information


- Supplemental haza

EUH208 Contains Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one, 2-Octyl-2H-isothiazol-3-on. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR





Revision 12/20/2022

- Biocidal Products Regulation (BPR)

Contains:

Biocidal active substances

Name of substance

Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one

1,2-benzisothiazol-3(2H)-one

Terbutryn

2-Octyl-2H-isothiazol-3-on

2.3 Other hazards

Of no significance.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture).

3.2 Mixtures

Description of the mixture:

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
quartz powder	CAS No 68855-54-9 EC No 310-127-6 272-489-0 REACH Reg. No 01-2119488518- 22-xxxx	2.5 - < 5	STOT RE 2 / H373	
1,2-benzisothiazol- 3(2H)-one	CAS No 2634-33-5 EC No 220-120-9 Index No 613-088-00-6 REACH Reg. No 01-2120761540- 60-xxxx	0.0015 - < 0. 015	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317 Aquatic Acute 1 / H400 Aquatic Chronic 2 / H411	
Terbutryn	CAS No 886-50-0	0.0015 - < 0. 015	Acute Tox. 4 / H302 Skin Sens. 1B / H317 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

BOU baumit.com

Revision 12/20/2022

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
2-Octyl-2H-isothiazol- 3-on	CAS No 26530-20-1 EC No 247-761-7 Index No 613-112-00-5 REACH Reg. No 01-2120768921- 45-xxxx	0.0015 - < 0. 015	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 2 / H330 Skin Corr. 1 / H314 Eye Dam. 1 / H318 Skin Sens. 1A / H317 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	
Reaction mass of 2- methyl-2H-isothiazol- 3-one and 5-chloro-2- methyl-2H-isothiazol- 3-one	CAS No 55965-84-9 Index No 613-167-00-5 REACH Reg. No 01-2120764691- 48-xxxx	0.0015 - < 0. 015	Acute Tox. 3 / H301 Acute Tox. 2 / H310 Acute Tox. 2 / H330 Skin Corr. 1C / H314 Eye Dam. 1 / H318 Skin Sens. 1A / H317 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
1,2-benzisothiazol- 3(2H)-one	Skin Sens. 1; H317: C ≥ 0.05 %	-	670 mg/kg	oral
Terbutryn	-	M-factor (acute) = 100 M-factor (chronic) = 100	500 mg/kg	oral
2-Octyl-2H-isothiazol- 3-on	Skin Sens. 1A; H317: C ≥ 0.0015 %	M-factor (acute) = 100 M-factor (chronic) = 100	125 mg/kg 300 mg/kg 0.5 mg/l/ 4h 0.27 mg/l/ 4h	oral dermal inhalation: vapour inhalation: dust/ mist
Reaction mass of 2- methyl-2H-isothiazol- 3-one and 5-chloro-2- methyl-2H-isothiazol- 3-one	Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	M-factor (acute) = 100 M-factor (chronic) = 100	100 mg/kg 50 mg/kg 0.5 mg/l/ 4h 0.05 mg/l/ 4h	oral dermal inhalation: vapour inhalation: dust/ mist

For full text of abbreviations: see SECTION 16.

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR



Revision

12/20/2022

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed None.

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes, Co-ordinate firefighting measures to the fire surroundings, Do not allow firefighting water to enter drains or water courses, Collect contaminated firefighting water separately, Fight fire with normal precautions from a reasonable distance

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



Revision

12/20/2022

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

- Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of effects

Protect against external exposure, such as

frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occu	Occupational exposure limit values (Workplace Exposure Limits)										
Coun- try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m ³]	Nota- tion	Sourc e
AT	2-octyl-2H-iso- thiazol-3-one	26530- 20-1	MAK		0.05				0.05	i, H	GKV
AT	reaction mass of: 5-chloro-2- methyl-2H-iso- thiazol-3-one and 2-methyl- 2H -isothiazol- 3-one (3:1)	55965- 84-9	МАК		0.05						GKV
AT	Silica, amorph- ous - silica fume, calcined diatomaceous earth	54-9	МАК		0.3					r	GKV

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

H absorbed through the skin

i inhalable fraction

r respirable fraction STEL short-term exposu

L short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)



Revision 12/20/2022

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR



Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3) Revision 12/20/2022

Notation TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture								
Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of exposure	Used in	Exposure time		
quartz powder	68855-54-9	DNEL	0.05 mg/ m ³	human, inhalat- ory	worker (in- dustry)	chronic - sys- temic effects		
1,2-benziso- thiazol-3(2H)-one	2634-33-5	DNEL	6.81 mg/ m ³	human, inhalat- ory	worker (in- dustry)	chronic - sys- temic effects		
1,2-benziso- thiazol-3(2H)-one	2634-33-5	DNEL	0.966 mg/ kg bw/day	human, dermal	worker (in- dustry)	chronic - sys- temic effects		
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2- methyl-2H-iso- thiazol-3-one	55965-84-9	DNEL	0.02 mg/ m ³	human, inhalat- ory	worker (in- dustry)	chronic - local effects		
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2- methyl-2H-iso- thiazol-3-one	55965-84-9	DNEL	0.04 mg/ m ³	human, inhalat- ory	worker (in- dustry)	acute - local ef- fects		

Relevant PNECs of components of the mixture									
Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time			
quartz powder	68855-54-9	PNEC	100 mg/l	aquatic organ- isms	sewage treat- ment plant (STP)	short-term (single instance)			
1,2-benziso- thiazol-3(2H)-one	2634-33-5	PNEC	4.03 µg/l	aquatic organ- isms	freshwater	short-term (single instance)			
1,2-benziso- thiazol-3(2H)-one	2634-33-5	PNEC	0.403 µg/l	aquatic organ- isms	marine water	short-term (single instance)			
1,2-benziso- thiazol-3(2H)-one	2634-33-5	PNEC	1.03 mg/l	aquatic organ- isms	sewage treat- ment plant (STP)	short-term (single instance)			
1,2-benziso- thiazol-3(2H)-one	2634-33-5	PNEC	49.9 µg/kg	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)			
1,2-benziso- thiazol-3(2H)-one	2634-33-5	PNEC	4.99 µg/kg	aquatic organ- isms	marine sedi- ment	short-term (single instance)			
1,2-benziso- thiazol-3(2H)-one	2634-33-5	PNEC	3 mg/kg	terrestrial or- ganisms	soil	short-term (single instance)			

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

baumit.com Revision 12/20/2022

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

Relevant PNECs of components of the mixture								
Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time		
2-Octyl-2H-iso- thiazol-3-on	26530-20-1	PNEC	2.2 µg/l	aquatic organ- isms	freshwater	short-term (single instance)		
2-Octyl-2H-iso- thiazol-3-on	26530-20-1	PNEC	0.22 µg/l	aquatic organ- isms	marine water	short-term (single instance)		
2-Octyl-2H-iso- thiazol-3-on	26530-20-1	PNEC	47.5 µg/kg	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)		
2-Octyl-2H-iso- thiazol-3-on	26530-20-1	PNEC	4.75 µg/kg	aquatic organ- isms	marine sedi- ment	short-term (single instance)		
2-Octyl-2H-iso- thiazol-3-on	26530-20-1	PNEC	8.2 µg/kg	terrestrial or- ganisms	soil	short-term (single instance)		
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2- methyl-2H-iso- thiazol-3-one	55965-84-9	PNEC	3.39 µg/l	aquatic organ- isms	freshwater	short-term (single instance)		
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2- methyl-2H-iso- thiazol-3-one	55965-84-9	PNEC	3.39 µg/l	aquatic organ- isms	marine water	short-term (single instance)		
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2- methyl-2H-iso- thiazol-3-one	55965-84-9	PNEC	0.23 mg/l	aquatic organ- isms	sewage treat- ment plant (STP)	short-term (single instance)		
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2- methyl-2H-iso- thiazol-3-one	55965-84-9	PNEC	0.027 mg/ kg	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)		
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2- methyl-2H-iso- thiazol-3-one		PNEC	0.027 mg/ kg	aquatic organ- isms	marine sedi- ment	short-term (single instance)		

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

Revision 12/20/2022

٦

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

Relevant PNECs of components of the mixture									
Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time			
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2- methyl-2H-iso- thiazol-3-one		PNEC	0.01 mg/ kg	terrestrial or- ganisms	soil	short-term (single instance)			



according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Eye/face protection



Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.



Revision

12/20/2022

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR



Revision 12/20/2022

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

liquid
different
characteristic
not determined
100 °C
this material is combustible, but will not ignite readily
not determined
not determined
not determined
not relevant
9 – 10
not determined
· ·

Water solubility	miscible in any proportion	
------------------	----------------------------	--

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	32 hPa at 25 °C
-----------------	-----------------

Density and/or relative density

Density	1,495 – 1,720 g/cm³		
Relative vapour density	information on this property is not available		

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR



Revision 12/20/2022

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant				
Other safety characteristics					
Miscibility	Completely miscible with water.				

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture							
Name of substance CAS No Exposure route ATE							
1,2-benzisothiazol-3(2H)-one	2634-33-5	oral	670 mg/kg				
Terbutryn	886-50-0	oral	500 mg/kg				
2-Octyl-2H-isothiazol-3-on	26530-20-1	oral	125 mg/kg				
2-Octyl-2H-isothiazol-3-on	26530-20-1	dermal	300 mg/kg				

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR



Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

Revisior
12/20/2022

Acute toxicity estimate (ATE) of components of the mixture						
Name of substance	ATE					
2-Octyl-2H-isothiazol-3-on	26530-20-1	inhalation: vapour	0.5 mg/l/4h			
2-Octyl-2H-isothiazol-3-on	26530-20-1	inhalation: dust/mist	0.27 mg/l/4h			
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2-methyl-2H- isothiazol-3-one	55965-84-9	oral	100 mg/kg			
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2-methyl-2H- isothiazol-3-one	55965-84-9	dermal	50 mg/kg			
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2-methyl-2H- isothiazol-3-one	55965-84-9	inhalation: vapour	0.5 mg/l/4h			
Reaction mass of 2-methyl-2H-iso- thiazol-3-one and 5-chloro-2-methyl-2H- isothiazol-3-one	55965-84-9	inhalation: dust/mist	0.05 mg/l/4h			

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Contains Reaction mass of 2-methyl-2H-isothiazol-3-one and 5-chloro-2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one, 2-Octyl-2H-isothiazol-3-on. May produce an allergic reaction

Classification Octylisothiazolinone:

Not skin sensitising based on results on similar mixtures tested using transfer principles according to CLP Regulation Article 9 (4); OECD 429 LLNA (mouse) - Not skin sensitising - S4565 / S4568 / S5145 / S5147.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

11.2 Information on other hazards

There is no additional information.

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

SECTION 12: Ecological information

12.1 Toxicity

Г

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (chronic) of components of the mixture							
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time		
quartz powder	68855-54-9	EC50	>1,000 mg/l	microorganisms	3 h		
1,2-benzisothiazol- 3(2H)-one	2634-33-5	EC50	13 mg/l	microorganisms	3 h		
Reaction mass of 2- methyl-2H-iso- thiazol-3-one and 5- chloro-2-methyl- 2H-isothiazol-3-one	55965-84-9	LC50	0.07 mg/l	fish	14 d		
Reaction mass of 2- methyl-2H-iso- thiazol-3-one and 5- chloro-2-methyl- 2H-isothiazol-3-one	55965-84-9	EC50	>0.18 mg/l	aquatic inverteb- rates	21 d		
Reaction mass of 2- methyl-2H-iso- thiazol-3-one and 5- chloro-2-methyl- 2H-isothiazol-3-one	55965-84-9	ErC50	45.6 μg/l	algae	120 h		

12.2 Persistence and degradability

Degradability of components of the mixture						
Name of sub- stance	CAS No	Process	Degradation rate	Time	Method	Source
1,2-benziso- thiazol-3(2H)- one	2634-33-5	carbon diox- ide genera- tion	62 %	4 d		ECHA
Reaction mass of 2- methyl-2H- isothiazol-3- one and 5- chloro-2- methyl-2H- isothiazol-3- one	55965-84-9	carbon diox- ide genera- tion	38.8 %	29 d		ECHA

12.3 Bioaccumulative potential

Data are not available.



Revision 12/20/2022

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR



Revision

12/20/2022

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

Bioaccumulative potential of components of the mixture					
Name of substance	CAS No	BCF	Log KOW	BOD5/COD	
1,2-benzisothiazol-3(2H)-one	2634-33-5	6.62	0.63 (pH value: 7, 10 °C)		
2-Octyl-2H-isothiazol-3-on	26530-20-1	2.92	2.61 (pH value: 7, 25 °C)		
Reaction mass of 2-methyl- 2H-isothiazol-3-one and 5- chloro-2-methyl-2H-iso- thiazol-3-one	55965-84-9	54	≥-0.34 – ≤0.63 (pH value: 7, 10 °C)		

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

Endocrine disrupting chemicals (EDC)				
Name of substance	CAS No	Combined cat- egory	Human health category	Wildlife cat- egory
Terbutryn	886-50-0	CAT1	CAT1	CAT3b

Legend

CAT1 Category 1 - evidence of endocrine disruption in at least one species using intact animals

CAT3b Category 3b - no evidence of endocrine disruption or no data available

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste codes/waste designations according to LoW

15 01 02: Plastic packaging

08 01 12: Waste paint and varnish other than those mentioned in 08 01 11

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

SECTION 14: Transport information

14.1 UN number or ID number

- 14.2 UN proper shipping name
- 14.3 Transport hazard class(es)
- 14.4 Packing group
- 14.5 Environmental hazards

not subject to transport regulations

not relevant

none

not assigned

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user There is no additional information.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Not subject to ADR, RID and ADN.

International Maritime Dangerous Goods Code (IMDG) - Additional information Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Name of sub- stance	Name acc. to in- ventory	CAS No	EC No	Type of re- gistration	Remarks	Restric- tion	No
SILIKONCOLOR	this product meets the criteria for clas- sification in accord- ance with Regula- tion No 1272/2008/ EC			1907/2006/ EC annex XVII	Liquid sub- stances or mixtures ful- filling the cri- teria for any of the follow- ing hazard classes or categories set out in An- nex I to Reg- ulation (EC) No 1272/ 2008:	R3	3



Revision 12/20/2022

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

Г

Dangerous substances with restrictions (REACH, Annex XVII)							
Name of sub- stance	Name acc. to in- ventory	CAS No	EC No	Type of re- gistration	Remarks	Restric- tion	No
					 (a) hazard (lasses 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1. 		
1,2-benzisothiazol- 3(2H)-one		2634- 33-5	220-120- 9				
Reaction mass of 2- methyl-2H-iso- thiazol-3-one and 5- chloro-2-methyl- 2H-isothiazol-3-one		55965 -84-9					
2-Octyl-2H-iso- thiazol-3-on		26530 -20-1	247-761- 7				
Terbutryn		886- 50-0					

Legend R3

1. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

- tricks and jokes, - games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:

can be used as fuel in decorative oil lamps for supply to the general public, and present an aspiration hazard and are labelled with H304.

4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the



Revision 12/20/2022

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR



Revision

12/20/2022

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

Legend

European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps - may lead to life-threatening lung damage"; (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1

December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage'; (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.';

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer **Register (PRTR)**

none of the ingredients are listed

Water Framework Directive (WFD)

List of pollutants (WFD)

Name of substance	CAS No	Listed in	Remarks
Reaction mass of 2-methyl-2H-isothiazol- 3-one and 5-chloro-2-methyl-2H-iso- thiazol-3-one		a)	
Terbutryn	886-50-0	b)	
Terbutryn	886-50-0	c)	
Terbutryn		a)	

Legend

C)

Indicative list of the main pollutants A) B)

List of priority substances in the field of water policy

Environmental Quality Standards for Priority Substances and certain other pollutants

Regulation on the marketing and use of explosives precursors

Not relevant.

Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

National regulations (Austria)

Ordinance on combustible liquids (VbF)

not assigned (flash point higher than 55 °C, water miscible)

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR



Revision 12/20/2022

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

Г

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the Interna- tional Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of sub- stances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR



Revision 12/20/2022

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

Abbr.	Descriptions of used abbreviations
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" de- veloped by the United Nations
GKV	Grenzwerteverordnung
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of An- nex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
log KOW	n-Octanol/water
LoW	List of Wastes
M-factor	Means a multiplying factor. It is applied to the concentration of a substance classi- fied as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
SVHC	Substance of Very High Concern
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

according to Regulation (EC) No. 1907/2006 (REACH)

SILIKONCOLOR

Version number: GHS 4.0 Replaces version of: 02/22/2022 (GHS 3)

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.



Revision 12/20/2022