Baumit ReClean

For preparation of dirty walls

- **For cleaning soiled surfaces.**
- **For removal of normal and stubborn dirt.**
- **Suitable for external and internal surfaces**

Product Overview

Concentrated façade cleaner with a high dirt and grease removal power.

Composition

Surface-active detergents, additives, water.

Properties

- Highly efficient and effective
- Non-foaming
- Easy to work with
- Biodegradable
- Long term effect

Application

- Use for the removal of common and stubborn dirt, such as grease or oil
- Adjustable intensity depending on the level of dirt on the surface
- For use indoors and outdoors for all mineral and organic surfaces
- Can also be used in conjunction with high-pressure cleaners

Technical Data

Color:	Clear blue liquid
density:	app. 1 kg/dm³
pH-value:	app. 8 - 9

	Baumit ReClean 5L
consumption	app. 0.1 - 0.2 l/m² (depending on substrate)

Delivery Format

5L canister, 1 pallet = 90 canisters

Storage

Store in dry conditions, in a closed container for up to 24 months.

Subsurface

Suitable for all mineral and organic finishes.

Subsurface Pre-treatment

Apply Baumit ReClean detergent to remove loose particles using a brush.

Processing

Dilution:Use Baumit ReClean detergent undiluted or diluted depending on the level of dirt on the façade / surface. Dilute with water to a ratio of 1:10.
Degree of dirt / Ratio of dilution:
Light dirt 1:10
Moderate dirt 1:5
Extreme dirt 1:1

Processing:
Apply Baumit ReClean with a hand sprayer, and for extreme dirt also use a hard brush to work the surface. Suitable for use with a high-pressure water cleaner on external facades.Clean surface for approximately 2-20 minutes depending on level of dirt, then wash down with lukewarm water or use a high pressure cleaner to rinse surface. In the case of severe contamination several applications may be required along with working the surface with a hard brush.

Baumit Ltd
Unit 2 Westmead, New Hythe Lane, Aylesford, Kent, ME20 6XJ, UK, - www.baumit.co.uk - contact@baumit.co.uk

Notes and General Informations

The air, material and substrate temperature must be above +5° C during application and processing.
Do not mix with any other materials.
Window, door and other surrounding structures should be thoroughly covered. Wash used tools or any possible spillages immediately after work with water. We also recommend to test the façade cleaner on a small area prior to full application

Written and oral application technology recommendations provided by us to assist the seller/processor are based on our experience and reflect the current state of the art in science and practical application know-how. However, it is understood that these recommendations are non-binding. They do not create any legal relationship or any ancillary obligations in connection with the sale contract. They do not release the buyer from its obligation to verify the suitability to our products for the intended purpose or use by itself.

Baumit Ltd
Unit 2 Westmead, New Hythe Lane, Aylesford, Kent, ME20 6XJ, UK, - www.baumit.co.uk - contact@baumit.co.uk