


# Baumit MonoTex

## Reinforced glass fibre mesh for use with MonoPlus



- Prevents cracks
- Highly alkali-resistant
- Easy to process

|                               |                                                                                                                                                                                                                                             |                                         |  |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|--|
| Product Overview              | Flexible and alkali-resistant, reinforced glass fibre mesh with a 10 x 10mm mesh size. MonoTex has been specifically designed for use with Baumit Monoplus. Weight: approx. 155 g / m².                                                     |                                         |  |
| Composition                   | Glass fibre mesh with special build to give tear and warp resistance. Dimensionally stable and alkali-resistant.                                                                                                                            |                                         |  |
| Properties                    | <div><div></div>Warp resistant.</div> <div><div></div>Alkal-resistant.</div> <div><div></div>System component of Baumit MonoPlus System.</div>                                                                                              |                                         |  |
| Application                   | Lay the Baumit MonoTex wet-on-wet into the MonoPlus render ensuring it is free from bubbles or folds. Position so that it lies within the upper third of the thickness of the MonoPlus coat. Do not cut on the roll.                        |                                         |  |
| Technical Data                | Mass per Unit Area:                                                                                                                                                                                                                         | 155 g/m²                                |  |
|                               | Mesh size:                                                                                                                                                                                                                                  | 10 x 10 mm (± 0,5 mm Tolerance) approx. |  |
|                               |                                                                                                                                                                                                                                             |                                         |  |
|                               |                                                                                                                                                                                                                                             | MonoTex 155 50m roll                    |  |
|                               | yield                                                                                                                                                                                                                                       | app. 45 m²/roll                         |  |
|                               | Consumption                                                                                                                                                                                                                                 | app. 1.1 m²/m²                          |  |
| Delivery Format               | Roll:50m2 (Width 1m), Pallet = 30 Rolls = 1,500 m²                                                                                                                                                                                          |                                         |  |
| Storage                       | MonoTex should be stored under normal climactic conditions. It should not be unusually dry nor unusually frozen for application. Ensure that MonoTex is stored so that it cannot be misshapen. Misshapen or damaged MonoTex cannot be used. |                                         |  |
| Quality Assurance             | Internal quality assurance is provided by the manufacturer's plant.                                                                                                                                                                         |                                         |  |
| Substrate                     | Ensure there is sufficient key in the MonoPlus before laying on the MonoTex mesh.                                                                                                                                                           |                                         |  |
| Processing                    | Position so that it lies within the upper third of the thickness of the MonoPlus coat. Taking care to not expose the mesh in the scratching back finished surface.                                                                          |                                         |  |
| Notes and General Information | If you need further information about this material or its handling, consult with our outside service experts about the details and the materials.                                                                                          |                                         |  |

Written and oral application technology recommendations provided by us to assist the seller/processor are based on our experience and reflect the current state of the art in science and practical application know-how. However, it is understood that these recommendations are non-binding. They do not create any legal relationship or any ancillary obligations in connection with the sale contract. They do not release the buyer from its obligation to verify the suitability to our products for the intended purpose or use by itself.